



EM99 DS Pro

For beginners and professional installers around the world

The EM99-DS-Pro is the universal blow-in machine in the professional segment. For two decades, it has been proving its performance and exceptional material versatility on construction sites of all types and sizes around the world, as well as in specialized applications.



► Unmatched Control Precision

The manual feed gate and the feed gate's speed control (optionally available with eight chambers instead of six) enable precise, material-specific dosing. This makes the EM99-DS-Pro exceptionally precise and flexible, particularly for core insulation and spray applications using lightweight insulation materials.

► Maximum Control at the Blowing Site

The standard FFB2000-Pro radio remote control, featuring high transmission reliability, allows for individual settings directly at the work site and optimizes the blowing process.

► Unique Ease of Transport

The removable filling attachment facilitates transport in small vehicles and allows for quick access for maintenance work.

► Proven Quality for Global Use

Thanks to its power connection, robust construction, and construction-site-ready tires, the EM99-DS-Pro has proven itself worldwide under a wide variety of job site conditions and stands for high reliability and durability.

► Excellent Value for the Money

The EM99-DS-Pro combines the performance and versatility of a large machine in a compact design, making it a cost-effective and popular choice for professional insulation installers.

Insulation material

Suitable for all loose insulation materials



Cellulose




Wood fibre



Wood shavings



EPS granulates



Perlite



Glass wool

Technical data

Measurements

Dimensions (L x W x H)	810 x 730 x 1325 mm
Unladen weight	111 kg
Hopper	0,26 m ³
Filling height	1325 mm
Airlock outlet	Ø NW75 (3")

Performance data

Rated power	3,6 kW
Air volume	280 m ³ /h
Dynamic pressure	330 mbar
Material processing speed	650 kg/h
Conveying height	30 m
Hose length	80 m

Characteristics

Material conditioning	rotating loosening mechanism with shredding arm
Air generator	high-performance radial compressor 2 x 1,45 kW
Power supply	230 V/50Hz/16A